

# HEXAGONIA

**HEXAGON**  
8 17/64" x 7 2/3"



**bone white**  
O8HHBW



**dove gray**  
O8HHDG



**gun powder**  
O8HHGP



**jet black**  
O8HHJB



**taupe back**  
O8HHTB



## HEXAGON BLEND



bone white  
22.5%

dove grey  
22.5%

taupe back  
22.5%

gun powder  
22.5%

jet black  
10%

### TECHNICAL FEATURES

|                                                                                       | standards                                                 | characteristics or properties                                           | declared values                                                                 |
|---------------------------------------------------------------------------------------|-----------------------------------------------------------|-------------------------------------------------------------------------|---------------------------------------------------------------------------------|
|  | ISO 10545-3                                               | assorbimento d'acqua<br>water absorption                                | < 0.5%                                                                          |
|  | ISO 10545-4                                               | resistenza alla flessione (R)<br>breaking strength                      | > 35 N/mm <sup>2</sup>                                                          |
|  | ISO 10545-13                                              | resistenza agli acidi<br>resistance to acid                             | GLA                                                                             |
|  | ISO 10545-12                                              | resistenza al gelo<br>frost resistance                                  | resiste<br>frost proof                                                          |
|  | ISO 10545-14                                              | resistenza alle macchie<br>stain resistance                             | 4                                                                               |
|  | ISO 10545-2                                               | planarità<br>surface flatness                                           | ± 0.5%                                                                          |
|  |                                                           | spessore<br>thickness                                                   | 11 mm (45x90, 80x80, 15x90)<br>10 mm (120x120, 60x120)<br>9.5 mm (30x60, 60x60) |
|  | DIN 51097<br>DIN 51130<br>ANSI A 137.1<br>DCOF BOT 3000 E | coefficiente d'attrito (scivolosità)<br>Dynamic coefficient of friction | A+B<br>R10<br>> 0.42                                                            |
|  | DIN 51097<br>DIN 51130                                    | coefficiente d'attrito (scivolosità)<br>Dynamic coefficient of friction | A+B+C<br>R11                                                                    |
|  |                                                           | variazioni cromatiche<br>color shade                                    | V2 variazione leggera<br>V2 slight variation                                    |