

HD PORCELAIN TILE



HD PORCELAIN TILE



12" x 24" NEXUS CLAY HD PORCELAIN TILE

HD PORCELAIN TILE



13" x 13" NEXUS CLAY HD PORCELAIN TILE
BFP1313NC



2" x 2" NEXUS CLAY HD PORCELAIN MOSAICS
BFP22NC



3" x 12" NEXUS CLAY HD PORCELAIN BULLNOSE
BFP312BNNC



12" x 24" NEXUS CLAY HD PORCELAIN TILE
BFP1224NC



16" x 32" NEXUS CLAY HD PORCELAIN TILE
BFP1632NC

HD PORCELAIN TILE



12" x 24" NEXUS ICE HD PORCELAIN TILE

HD PORCELAIN TILE



13" x 13" NEXUS ICE HD PORCELAIN TILE
BFP1313NI



2" x 2" NEXUS ICE HD PORCELAIN MOSAICS
BFP22NI



3" x 12" NEXUS ICE HD PORCELAIN BULLNOSE
BFP312BNNI



12" x 24" NEXUS ICE HD PORCELAIN TILE
BFP1224NI



16" x 32" NEXUS ICE HD PORCELAIN TILE
BFP1632NI

HD PORCELAIN TILE



12" x 24" NEXUS MICA HD PORCELAIN TILE

HD PORCELAIN TILE



13" x 13" NEXUS MICA HD PORCELAIN TILE
BFP1313NM



2" x 2" NEXUS MICA HD PORCELAIN MOSAICS
BFP22NM



3" x 12" NEXUS MICA HD PORCELAIN BULLNOSE
BFP312BNM



12" x 24" NEXUS MICA HD PORCELAIN TILE
BFP1224NM



16" x 32" NEXUS MICA HD PORCELAIN TILE
BFP1632NM

HD PORCELAIN TILE



12" x 24" NEXUS GRAPHITE HD PORCELAIN TILE

HD PORCELAIN TILE



13" x 13" NEXUS GRAPHITE HD PORCELAIN TILE
BFP1313NG



2" x 2" NEXUS GRAPHITE HD PORCELAIN MOSAICS
BFP22NG



3" x 12" NEXUS GRAPHITE HD PORCELAIN BULLNOSE
BFP312BNNG



12" x 24" NEXUS GRAPHITE HD PORCELAIN TILE
BFP1224NG



16" x 32" NEXUS GRAPHITE HD PORCELAIN TILE
BFP1632NG

HD PORCELAIN TILE

DESCRIPTION	LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
12" x 24" NEXUS HD PORCELAIN TILE	64.12	8	15.50	32	496.00
13" x 13" NEXUS HD PORCELAIN TILE	52.42	13	15.28	46	702.88
16" x 32" NEXUS HD WALL TILE	62.58	4	13.78	24	330.72
2" x 2" NEXUS HD PORCELAIN MOSAICS	38.45	10	9.69	48	465.12
3" x 12" NEXUS HD PORCELAIN BULLNOSE	16.46	20	n/a	n/a	n/a

DESCRIPTION	METHOD	UNIT	13" x 13"	12" x 24"
THICKNESS		mm – in	9.5 mm – 3/8"	9.5 mm – 3/8"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	4	4
SCRATCH HARDNESS		(Mohs)	7	7
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 450	≥ 450
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.60	≥ 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.80	≥ 0.80
DCOF (WET)	ANSI B101.3		≥ 0.42	≥ 0.42
SHADE VARIATION			V3	V3

