



Raffino, Glazed Ceramic.

A decadent combination of refined marble looks, modern textures and elongated profiles.

#### Colors at a Glance


The Raffino collection offers exclusive patterned designs combined with the earthy nuances of premium marbles. These neutral colors are easily adaptable to elegant design spaces.



Calacatta Dolce



Bianco Vita



Statuario Valore



Onyx Suave

#### Formats, Patterns and Finishes at a Glance

A collection of matte rectified and pressed wall tiles which come in a flat surface design as well as a three three-dimensional designs, which include irregular bamboo channels, woven contours and artisanal surfaces.



12 x 36 in Rectified Matte



12 x 36 in Curva Rectified Matte



12 x 36 in Alto Rectified Matte



3 x 12 in Artisan Rectified Matte



#### Raffino, Calacatta Dolce

An elegant pattern of winding golden veins gracefully elongated with complementary three dimensional patterns. A refined and sophisticated expression of luxuriousness.

12 x 36 in Alto Rectified

Matte | BFC1236RAC



3 x 12 in Artisan Pressed Matte | BFC312RAC



12 x 36 in Rectified Matte | BFC1236RC



12 x 36 in Curva Rectified Matte | BFC1236RCC

### Raffino, Onyx Suave

An ethereal character defined by neutrality and elegance, suitable for classic and contemporary interiors thanks to its extraordinary translucency.



3 x 12 in Artisan Pressed Matte | BFC312RAO



12 x 36 in Rectified Matte | BFC1236RO



Matte | BFC1236RAO



12 x 36 in Curva Rectified Matte | BFC1236RCO



#### Raffino, Bianco Vita

A delicate and luminous pattern with subtle white and grey veining, an icon of endless elegance thanks to its timeless aesthetic.

12 x 36 in Alto Rectified


Matte | BFC1236RAB



3 x 12 in Artisan Pressed Matte | BFC312RAB



12 x 36 in Rectified Matte | BFC1236RB



12 x 36 in Curva Rectified Matte | BFC1236RCB

### Raffino, Statuario Valore

The refined look of Statuario marble creates a timeless style that reflects contemporary design with incomparable elegance and harmony.



3 x 12 in Artisan Pressed Matte | BFC312RAS



12 x 36 in Rectified Matte | BFC1236RS




12 x 36 in Curva Rectified Matte | BFC1236RCS




12 x 36 in Alto Rectified Matte | BFC1236RAS





12 x 36 in Raffino Bianco Vita Alto Matte Rectified Tile On the floor: 12 x 24 in / La Marca Statuarietto, Honed Rectified Tile







# Packaging Information

Key logistical details including item codes and product specifications.

Raffino Product & Packaging Information

	ACTUAL	THICKNESS	BIANCO VITA	CALACATTA DOLCE	ONYX SUAVE	STATUARIO VALORE	LBS	KGS	PCS	SQFT	M <sup>2</sup>	BXS	SQFT	M <sup>2</sup>
	DIMENSIONS		ITEM CODE	ITEM CODE	ITEM CODE	ITEM CODE	BOX	BOX	BOX	BOX	BOX	SKID	SKID	SKID
12 x 36 in / 30 x 90 cm RECTIFIED GLAZED CERAMIC TILE	300 x 900 mm	10 mm	4000-0272-0	4000-0274-0	4000-0275-0	4000-0273-0	51.37	23.3	5	14.53	1.35	20	290.6	27
12 x 36 in / 30 x 90 cm ALTO RECTIFIED GLAZED CERAMIC TILE	300 x 900 mm	10 mm	4000-0264-0	4000-0266-0	4000-0267-0	4000-0265-0	51.37	23.3	5	14.53	1.35	20	290.6	27
12 x 36 in / 30 x 90 cm CURVA RECTIFIED GLAZED CERAMIC TILE	300 x 900 mm	10 mm	4000-0268-0	4000-0270-0	4000-0271-0	4000-0269-0	51.37	23.3	5	14.53	1.35	20	290.6	27
3 x 12 in / 7.5 x 30 cm ARTISAN PRESSED GLAZED CERAMIC TILE	75 x 300 mm	9 mm	4000-0276-0	4000-0278-0	4000-0279-0	4000-0277-0	24.84	11.27	36	8.72	0.81	64	558.19	51.84

## Technical Information

Tile collection performance based on industry standards.

Technical In	formation		
$\Diamond$	WATER ABSORPTION	ANSI / ISO - (%)	10% ≤E ≤18% - P4
	ABRASION RESISTANCE	ANSI / ISO	CLASS 0
202	SCRATCH HARDNESS	ANSI / ISO - (Mohs) >230	4
8/8	BREAKING STRENGTH	>950 ANSI - (lbf) ISO - (N)	
	SHADE VARIATION		V2
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	MATTE N/A MATTE N/A
	CHEMICAL RESISTANCE	ANSI / ISO	CLASS B
Z	STAIN RESISTANCE	ANSI ISO	CLASS B CLASS 4
*	FROST RESISTANCE	ANSI / ISO	NOT RESISTANT

Test values are based on ANSI / ISO standards according to: ISO 13006 - G - Group Billb - EN 14411-G - GROUP Billb- ANSI A137.1 Non-Vitreous P4 Class Variances in test values can occur in different production lots.

## Usage Recommendation


Manufacturerer's recommendations for suitable applications.

Usage Recommendations*		MATTE GLAZED CERAMIC			
APPLICATION		WALL	FLOOR		
INTERIOR	RESIDENTIAL	•			
	COMMERCIAL	•			
	HEAVY COMMERCIAL				
EXTERIOR	RESIDENTIAL / COMMERCIAL				

<sup>\*</sup> These recommendations are not defined by ANSI/ISO standards.



- Not for use on any floor application under any circumstances
- Does not require sealing
- Install with a 1/16" grout joint as it is rectified
- No more than 1/3 offset per the TCNA recommendations
- Regular thinset does not need to be modified as it is a P4 body
- If using a high contrast grout, refer to the grout manufacturer's instructions regarding testing for staining. Note: this is a grout feature, not a tile failure, as manufacturer's ask for stain testing even on glass with some high performance grouts
- For interior use only, not frost proof due to the wall body



- when installing the ALTO style of the Raffino series, please look on the backside of the tile and install using the arrows indicted on the back of each piece. All arrows need to be pointed into the SAME direction when installing to line up correctly as indicted in the photos to the left.
- It does not matter which direction the arrow faces when installing, as long as each arrow is facing the same direction during application.