









RIVIERA MATTE (FLOOR TILE)

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	Conformity
 Breaking strength	ISO 10545-4	≥ 35 N/mm ²	Conformity
 Abrasion resistance	ISO 10545-7	PEI	PEI 4
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration.	Conformity
 Chemical resistance	ISO 10545-13		GA GLA
 Thermal shock resistance	ISO 10545-5		Conformity
 Dynamic coefficient of friction	BOT 3000E	DCOF ≥ 0.42	0.48
 Slight Variation	See Below		V3

SIZES FEATURED IN THE MATTE FINISH:

- 8" x 8" and 8.79" x 9.9" Hexagon -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4









For the best product laying results, material from at least three boxes should be mixed.

CERAMICHE D'ARTE

www.bfceramics.com

RIVIERA

GLOSSY/MATTE (WALL TILE)

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	> 10%	Conformity
 Breaking strength	ISO 10545-4	≥ 12 N/mm ² ≥ 600 N	Conformity
 Abrasion resistance	ISO 10545-7		
 Frost resistance	ISO 10545-12	Not Applicable	
 Chemical resistance	ISO 10545-13	No samples must show ruptures or noticeable surface alteration.	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable - Wall Tile Only	
 Slight Variation	See Below	V1: Black, White V3: Blue, Burgundy, Dark Taupe, Deep Green, Grey, Light Pink, Turquoise	V1/V3

SIZES FEATURED IN THE GLOSSY/MATTE FINISH:

- 2.5" x 10", 4" x 16", 5" x 5" and Quarter Rounds -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4

For the best product laying results, material from at least three boxes should be mixed.

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.

CERAMICHE D'ARTE

www.bfceramics.com