

SAN MARCOS POLISH

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT	
♦♦♦ ♦♦♦ Water absorption of the body	ISO 10545-3	≤ 0.5%	Conformity	
Breaking strength	ISO 10545-4	≥ 35 N/mm^2	Conformity	
Abrasion resistance	ISO 10545-7	PEI 2 - Nero, Blue, Verde PEI 3 - Bianco, Fango, Tortora	PEI 2-3 *See Standards	
Frost resistance	ISO 10545-12	No samples must show ruptures or noticable surface alteration	Conformity	
Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity	
Thermal shock resistance	ISO 10545-5		Conformity	
Dynamic coefficient of friction	BOT 3000E	Not Applicable; Wall Tile Only	N/A	
Slight Variation	See Below	V2 - Bianco, Nero, Tortora V3 - Blue, Verde, Fango	V2-3 *See Standards	
Uniform appearance Slight Variation Woderate Variation V1 V2 V3 V4				

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com



SAN MARCOS **MATTE**

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT	
♦♦♦ Water absorption of the body	ISO 10545-3	≤ 0.5%	Conformity	
Breaking strength	ISO 10545-4	≥ 35 N/mm^2	Conformity	
Abrasion resistance	ISO 10545-7		PEI 4	
Frost resistance	ISO 10545-12	No samples must show ruptures or noticable surface alteration	Conformity	
Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity	
Thermal shock resistance	ISO 10545-9		Conformity	
Dynamic coefficient of friction	BOT 3000E	ANSI A326.3:2019	0.47	
Slight Variation	See Below	V2 - Bianco, Nero, Tortora V3 - Blue, Verde, Fango	V2-3 *See Standards	
Uniform appearance Slight Variation Woderate Variation V3 V4				

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED



www.bfceramics.com