









ELEGANCE OPULENT GREY MATTE

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\%$
 Breaking strength	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	$\geq 35 \text{ N/mm}^2$
 Abrasion resistance	ISO 10545-7	Determination of Resistance to Surface Abrasion	PEI 5
 Frost resistance	ISO 10545-12	Frost Resistance	Conformity
 Chemical resistance	ISO 10545-13	Resistance to Acid	GLA
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	ANSI A137.1-2012	0.57
 Slight Variation	See Below		V2



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation











V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

CERAMICHE  D'ARTE

www.bfceramics.com

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\%$
 Breaking strength	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	$\geq 35 \text{ N/mm}^2$
 Abrasion resistance	ISO 10545-7	Determination of Resistance to Surface Abrasion	PEI 4
 Frost resistance	ISO 10545-12	Frost Resistance	Conformity
 Chemical resistance	ISO 10545-13	Resistance to Acid	GLA
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	ANSI A137.1-2012	N/A
 Slight Variation	See Below		V2



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.

CERAMICHE  D'ARTE

www.bfceramics.com