

ELEGANCE II NERO MARQUINA MATTE

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
Image: Water absorption of the body	ISO 10545-3	≤ 0.5%	Conformity
Breaking strength	ISO 10545-4	≥ 35 N/mm^2	Conformity
Abrasion resistance	ISO 10545-7		PEI 4
Frost resistance	ISO 10545-12	No samples must show ruptures or noticable surface alteration	Conformity
Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
Thermal shock resistance	ISO 10545-5		Conformity
Dynamic coefficient of friction	BOT 3000E	ANSI A 326.3-2017	0.50
Slight Variation	See Below		V2

V1

Uniform appearance Slight Variation V2



Substantial Variation

V4

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

CERAMICHE SD'ARTE

www.bfceramics.com




ELEGANCE II NERO MARQUINA POLISHED

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
Water absorption of the body	ISO 10545-3	≤ 0.5%	Conformity
Breaking strength	ISO 10545-4	≥ 35 N/mm^2	Conformity
Abrasion resistance	ISO 10545-7		PEI 3
Frost resistance	ISO 10545-12	No samples must show ruptures or noticable surface alteration	Conformity
Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
Thermal shock resistance	ISO 10545-5		Conformity
Dynamic coefficient of friction	BOT 3000E		
Slight Variation	See Below		V2

Uniform appearance

Slight Variation



Substantial Variation

V4

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.

CERAMICHE SD'ARTE

www.bfceramics.com

2005 International Parkway Fredericksburg, VA 22406 | Phone: 540-286-3000 | Fax: 540-286-3010