



B&F Ceramics Design Showroom now has the **Guardia Surface Protection** in stock!

## PRODUCT DESCRIPTION

Guardia is the most balanced solution PET Fibre delivering strong multi layered protection, flexible usage and lower cost versus more expensive solutions that are heavier and least likely to be reused. Guardia is a multi-layered, multi-use and reusable protection mat. Since it is quick to install, requires no tape to connect overlaps and is reusable, it saves you time and money. 100% recycled and pollutant free production, it is environmentally friendly and thermally disposable.

# **USES**

- Guardia is tear resistant, waterproof, breathable & flexible and has an anti-slip, self adhesive coating on the bottom that keeps it in place!
- Simply roll it out, overlap & bend it around corners, frames, baseboards and more.
- Use it on a variety of surfaces such as ceramic, natural stone, hardwood, stairs, counters, tables, furniture and much more!

# CONTACT

Please contact your B&F Ceramics Sales Representative for more information.







## SURFACE PROTECTION

A multi-layered, multi-use and reusable protection mat for your job site.





Protect your valuable floors and hard surfaces against tools, sharp debris, paint, liquids, dirt, and other hazards. Suitable for flooring, stairs, counter tops, appliances, tables, furniture, plumbing fixtures and a variety of other applications.

······	$\Diamond$	<b>8</b> 8
BREATHABLE	WATERPROOF	RESISTANT
		50°5
ANTI SLIP	NO TAPE NEEDED	EASILY APPLIED

BOX QUANTITY	24 Rolls	18 Rolls
SIZE / DIMENSIONS	36 in x 100 ft / 91 cm x 30.5 m	36 in x 50 ft / 91 cm x 15.25 m
ITEM CODE	#G300	#G150
COVERAGE	300 sqft / 27.75 m <sup>2</sup>	150 sqft / 13.88 m <sup>2</sup>

#### **USAGE & CARE INSTRUCTIONS**

- Ensure you turn off floor heating before laying Guardia.
- Clean the underlaying surface for better adhesion and to maximize reusage adhesion.
- The product should be laid down with an overlap of 4 in / 10 cm.
- Keep ambient temperature between 50-86 F
  / 10-30 C and humidity at less than 60%.
- Protect against direct sun exposure for prolonged periods of time.
- Ensure surfaces to be protected are dry before applying this product.
- Do not use on surfaces that have been treated with any solvent-based products before they have been properly cured per the manufacturer's guidelines and no longer emit solvent vapor.
- Avoid placing heavy objects directly on the surface protection mat for prolonged periods of more than 24 hours.
- Taping down the start and end of the rolls is recommended. To ensure clean removal and possible residual adhesive, this product should not be left on any unfinished surface for more than 60 consecutive days.
- This product can be thermally disposed of, where available.
- If the use and care of the product and environment has changed or caused adhesion to the floor surface it can be cleaned using a kitchen cloth, a small amount of neutral PH soap and lukewarm water. Using the product outside of the recommended usage and care conditions will void warranty and liability.